



Dimensions						
Size	3"	4"	6"	8"	10"	12"
L	9-1/2"	10"	11-1/2"	12-1/2"	14-3/4"	14-7/8"
H	11-5/8"	13-3/4"	17-15/16"	21-7/16"	25-3/8"	28-3/4"
D	---	12"	12"	12"	12"	12"

Notes:

1. Pressure rating: 300PSI
2. UL Listed and FM Approved



No.	Description	Material Specifications
1	Body	Ductile Iron, ASTM A536 65-45-12
2	Wedge	Ductile Iron, EPDM Encapsulated
3	Wedge Nut	ASTM C67400
4	Stem	Stainless Steel, AISI 420
5	Gasket	EPDM
6	Bonnet	Ductile Iron, ASTM A536 65-45-12
7	O-ring	EPDM
8	Thrust Ring	ASTM C67400
9	O-ring	EPDM
10	Gland	Ductile Iron, ASTM A536 65-45-12
11	O-ring	EPDM
12	Dustproof Ring	EPDM
13	Bolts	Carbon Steel Gr8.8
14	Operating Nut	Ductile Iron, ASTM A536 65-45-12
15	Plug (Optional)	Malleable Iron

NRS Gate Valve 3" to 12", MJ x MJ Ends

F0233-300

Rev. A



WEFLO VALVE LLC

E-mail: info@weflovalve.com

Website: www.weflo.com / www.weflovalve.com